



Lithium Carbonate, Technical Grade

CAS No. 554-13-2

QS-PDS-1051 Revision: 04

Date of Last Revision: July 7, 2022

Formula: Li_2CO_3

Appearance: An odorless white, free-flowing powder

Application: A free-flowing, odorless white powder with guaranteed 99.3 wt.% purity and a relatively fine particle size. Technical Grade product is a higher purity grade for use as a precursor in making critical battery materials, is useful in the manufacture of glass, frits, other ceramics and a variety of specialized applications.

Product Specifications:	Li_2CO_3 , wt. %	99.3	min
	Loss @ 500° C	0.6	max
	Na_2O , wt. %	0.2	max
	CaO , wt. %	0.05	max
	SO_4 , wt. %	0.1	max
	Fe_2O_3 , wt. %	0.003	max
	Cl, wt. %	0.01	max
	Acid Insolubles, wt. %	0.02	max
	H_2O^* , wt. %	0.6	max
	K_2O	0.005	max

* Value (as weight percent loss) determined by drying at 500°C for 30 minutes.

Other Data:	Loose Bulk Density	0.50 g/cc
	Tapped Bulk Density	0.75 g/cc*

* Particle size and density are made to customer requirements.

Physical Properties:	Molecular Weight	73.89
	Melting Point	720°C

Water Solubility: Lithium carbonate solubility varies between 8-12 gm/L depending on temperature of the water. Water solubility is 1.3 wt. % @ 20°C



Toxicity/Safety Data *Information on toxicity, safety, handling, storage and disposal*
Handling / Storage / Disposal: *is contained in the Safety Data Sheet (SDS) for this product.*

Shipping Containers:

- 100 Kg of product in a polyethylene-lined fiber drum. Four (4) fiber drums per pallet. 400 Kg per pallet.
- 20 Kg of product in a paper bag. Forty-four (44) bags per pallet. 880 Kg per pallet.
- 25 Kg of product in a paper bag. Forty (40) bags per pallet. 1000 Kg per pallet.
- 50 lbs of product in a paper bag. Forty-four (44) bags per pallet. 2200 lbs per pallet.
- 450 Kg of product in a supersack, stacked two (2) high. 900 Kg per pallet.
- 900 Kg of product in a supersack, single stacked. 900 Kg per pallet.

Shipping Limitations: Shipments of lithium carbonate require no hazardous shipping labels.

Post, Parcel, Air, Water, Rail, Truck
Acceptable within each carrier's weight limits and packaging requirements.