



Lithium Chloride, Industrial Grade

CAS No. 7447-41-8

QS-PDS-1056 Revision: 04

Date of Last Revision: June 12, 2024

Formula: LiCl

Appearance: Free-flowing white crystals.*

* Occasional dark particles may be visible and scattered in the product. The particles have no detectable effect on product purity and will not be cause for rejection.

Application: Molten salt chemistry and metallurgy, brazing fluxes, catalyst for organic oxidation reactions, electrolyte in dry cells used in low temperatures, and stabilizer in textile fiber spinning solutions. Solubilizer for polyamides and cellulose when used with amide solvents, chlorinating agent for steroid agents. Desiccant for drying applications, tracer in wastewater.

Product Specifications:	LiCl, wt. %	98.5	min
	H ₂ O, wt. % **	0.6	max
	Alkalinity as Li ₂ CO ₃ , wt. %	0.03	max
	KCl, wt. %	0.5	max
	NaCl, wt. %	0.6	max
	CaCl ₂ , wt. %	0.02	max
	SO ₄ , wppm	100	max
	Fe ₂ O ₃ , wppm	10	max
	Acid Insolubles, wppm	100	max

** Value (as weight percent loss) determined by drying @ 350°C for 45 minutes.

Physical Properties:	Molecular Weight	42.39
	Melting Point	608°C
	Boiling Point	1382°C
	Specific Heat @ 25°C	0.288 cal/g/°C
	Standard Heat of Formation	-97.70 kcal/mole
	Heat of Solution @ 18°C	-8.49 kcal/mole
	Heat of Fusion	4.7 kcal/mole
	Density @ 25°C	2.068 g/cm ³

Solubility: Water solubility is 45.4 wt. % @ 25°C. Moderate solubility in polar organic solvents.

Toxicity / Safety Data / Handling / Storage / Disposal: *Information on toxicity, safety, handling, storage and disposal is contained in the Safety Data Sheet (SDS) for this product.*



Shipping Containers:

- 50 Kg of product in a polyethylene-lined fiber drum. Nine (9) fiber drums per pallet.
- 200 Kg of product in a polyethylene-lined fiber drum. Four (4) fiber drums per pallet.
- 1000 Kg of product, in a lined super sack on a pallet.

Shipping Limitations: Shipments of lithium chloride require no dangerous goods shipping labels.

Post, Parcel, Air, Water, Rail, Truck	Acceptable within each carrier's weight limits and packaging requirements.
---	---