

Lithium Carbonate, Industrial Grade CAS No. 554-13-2

QS-PDS-1062 Revision: 04 Date of Last Revision: June 12, 2024

Formula: Li₂CO₃

Appearance: An odorless white, free-flowing powder

Application: A free-flowing, odorless white powder with guaranteed 99.0 wt. %

purity and a relatively fine particle size. Industrial Grade product is a useful in the manufacture of glass, frits, other ceramics and a

variety of specialized applications.

Product Specifications: Li₂CO₃, wt. % 99.0 min

Physical Properties: Molecular Weight 73.89

Melting Point 720°C

Water Solubility: Lithium carbonate solubility varies between 8-12 gm/L depending

on temperature of the water. Water solubility is 1.3 wt. % @ 20°C

Toxicity/Safety Data Information on toxicity, safety, handling, storage and disposal is **Handling / Storage / Disposal:** contained in the Safety Data Sheet (SDS) for this product.

Shipping Containers:

- 100 Kg of product in a polyethylene-lined fiber drum. Four (4) fiber drums per pallet. 400 Kg per pallet.
- 20 Kg of product in a paper bag. Forty-four (44) bags per pallet. 880 Kg per pallet.
- 25 Kg of product in a paper bag. Forty (40) bags per pallet. 1000 Kg per pallet.
- 50 lbs of product in a paper bag. Forty-four (44) bags per pallet. 2200 lbs per pallet.
- 450 Kg of product in a supersack, stacked two (2) high. 900 Kg per pallet.
- 900 Kg of product in a supersack, single stacked. 900 Kg per pallet.

^{*} Value (as weight percent loss) determined by drying at 500°C for 30 minutes.



Shipping Limitations: Shipments of lithium carbonate require no dangerous goods

shipping labels.

Post, Parcel, Air, Water,

Acceptable within each carrier's weight limits

and packaging requirements. Rail, Truck