

Lithium Hydroxide, Monohydrate Micronized, 5 µm CAS No. 1310-66-3

QS-PDS-2061 Revision: 04 Date of Last Revision: June 12, 2024

Formula: LiOH.H₂O

Appearance: White, fine powder to 5±1.5 μm.

Application: A free-flowing granular solid used in the production of

cathode active material for lithium-ion batteries.

Product Specifications: LiOH, wt. % 56.5 min

CO₂, wt. % 0.5 max Ca, ppm 50 max Fe, ppm 10 max Na, ppm 50 max SO₄, ppm 150 max CI, ppm 20 max Magnetic Impurities, ppb 100 max D50 (Dry), µm 3.5 min 6.5 max

Other Data: Loose Bulk Density 0.293 g/mL

Tapped Bulk Density 0.491 g/mL

Physical Properties: Odor Odorless

pH (1% Solution) @ 25°C: >13

Specific Gravity 1.5 g/cc Molecular Weight 41.96



Water Solubility: % by wt. @ 25°C (77°F): 10

Toxicity/Safety Data Information on toxicity, safety, handling, storage and disposal Handling / Storage / Disposal: is contained in the Safety Data Sheet (SDS) for this product.

Shipping Containers: •

250 Kg super sack double stacked on a pallet, 10 pallets per 20' container, 20 pallets per 40' container

350 Kg super sack single stack on a pallet, 10 pallets per 20' container, 20 pallets per 40' container

Shipping Limitations:

Shipments of lithium hydroxide are described as "Lithium Hydroxide, UN 2680." All shipments are Hazard Class 8 and require "Corrosive" labels.

Not acceptable Post Parcel, Air Restricted quantities

Sea Class 8 (IMDG) Road Class 8 (DOT/ADR)