

Lithium Hydroxide, Monohydrate Micronized, 10 µm CAS No. 1310-66-3

QS-PDS-2062 Revision: 03 Date of Last Revision: June 12, 2024

Formula: LiOH.H<sub>2</sub>O

**Appearance:** White, fine powder to 11±2 μm.

Application: A free-flowing granular solid used in the production of

cathode active material for lithium-ion batteries.

Product Specifications: LiOH, wt. % 56.5 min

> CO2, wt. % 0.5 max Ca, ppm 70 max 10 max Fe, ppm Na, ppm 50 max SO4, ppm 150 max CI, ppm 20 max Magnetic Impurities, ppb 100 max

> D50 (Dry), µm 9.0 min 13.0 max

Loose Bulk Density 0.355 g/mL Other Data:

> Tapped Bulk Density 0.651 g/mL

**Physical Properties:** Odorless Odor

> (1% Solution) @ 25°C: >13 Hq

Specific Gravity 1.5 g/cc Molecular Weight 41.96



**Solubility:** % by wt. @ 25°C (77°F): 10

Handling / Storage / Disposal: is contained in the Safety Data Sheet (SDS) for this product.

Shipping Containers: •

250 Kg super sack double stacked on a pallet, 10 pallets per 20' container, 20 pallets per 40' container

350 Kg super sack single stack on a pallet, 10 pallets per 20' container, 20 pallets per 40' container

**Shipping Limitations:** 

Shipments of lithium hydroxide are described as "Lithium Hydroxide, UN 2680." All shipments are Hazard Class 8 and require "Corrosive" labels.

Post Not acceptable Restricted quantities Parcel, Air

Sea Class 8 (IMDG) (DOT/ADR) Road Class 8