

Lithium Hydroxide, Monohydrate Micronized, 15 µm CAS No. 1310-66-3

QS-PDS-2063 Revision: 03 Date of Last Revision: June 12, 2024

Formula: LiOH.H<sub>2</sub>O

**Appearance:** White, fine powder to 15±2 μm.

**Application:** A free-flowing granular solid used in the production of

cathode active material for lithium-ion batteries.

Product Specifications: LiOH, wt. % 56.5 min

CO2, wt. % 0.5 max Ca, ppm 50 max 10 max Fe, ppm Na, ppm 50 max S, ppm 50 max Zn, ppm 10 max CI, ppm 20 max Magnetic Impurities, ppb 100 max 13.0 min 17.0 max D50 (Dry), µm

Other Data: Loose Bulk Density 0.39 g/ml

Tapped Bulk Density 0.74 g/ml

Physical Properties: Odor Odorless

pH (1% Solution) @ 25°C: >13

Specific Gravity 1.5 g/cc Molecular Weight 41.96



Water Solubility: % by wt. @ 25°C (77°F): 10

Handling / Storage / Disposal: is contained in the Safety Data Sheet (SDS) for this product.

Shipping Containers: •

250 Kg super sack double stacked on a pallet, 10 pallets per 20' container, 20 pallets per 40' container

350 Kg super sack single stack on a pallet, 10 pallets per 20' container, 20 pallets per 40' container

**Shipping Limitations:** 

Shipments of lithium hydroxide are described as "Lithium Hydroxide, UN 2680." All shipments are Hazard Class 8 and require "Corrosive" labels.

Post Not acceptable Restricted quantities Parcel, Air

Sea Class 8 (IMDG) Road Class 8 (DOT/ADR)